



Part No. 1510151



Part No. 1510158




Part No. 1510165




Front

Back

Part No. 1510161



Part No. 1510920



Part No. 1510921

Features

- Maximum inlet pressure of 14kPa
- Ideal for low pressure applications such as flueless space heaters and barbecues
- Approved by the Australian Gas Association
- Optional safety cap available seperately
- Available in wall, floor & flush mount options

Certifications



Specifications

Part No.	Description	Connection	AGA No.
1510151	Chrome plated floor socket	1/2" BSPT Female Max inlet pressure: 14kPa	6421
1510158	Nickel plated wall mount socket	1/2" BSPT Male Max. inlet pressure: 14kPa	6421
1510165	Nickel plated straight socket	1/2" BSPT Female Max inlet pressure: 14kPa	6421
1510161	Natural brass socket	1/4" BSPP Male	N/A

Kits Available

Part No.	Description	Connection	AGA No.
1510920	<ul style="list-style-type: none"> • Chrome plated floor socket & stainless steel cover plate • Flush wall-mount outlet for low pressure appliances such as flueless space heaters, barbecues or cookers • Bracket, dust cap and 2x mounting screws included 	1/2" BSPP Male Max inlet pressure: 14kPa	6421
1510921	<ul style="list-style-type: none"> • Nickel plated floor socket & stainless steel cover plate • Flush wall-mount outlet for low pressure appliances such as flueless space heaters, barbecues or cookers • Bracket, dust cap and 2x mounting screws included 	1/2" BSPT Female Max inlet pressure: 14kPa	6421